

呼び番号	内輪内径d	外輪外径D	外輪内径d1	内輪外径D1	高度H	基本動定格荷重	基本静定格荷重	許容回転数		鋼球	
								rpm			
								グリース	オイル	个数	直径
F2-6	2	6	2	6	3	100	78	11800	16000	6	1
F3-8M	3	8	3.2	7.8	3.5	600	480	11000	15000	6	1.588
F4-9M	4	9	4.2	8.8	4	800	520	8000	12000	6	1.588
F4-10M	4	10	4.2	9.8	4	658	580	6000	10000	6	1.588
F5-10M	5	10	5.2	9.8	4	950	830	5100	8100	7	1.588
F5-11M	5	11	5.2	10.8	4.5	988	880	5000	8000	7	1.588
F5-12M	5	12	5.2	11.8	4	988	880	5000	8000	7	1.588
F6-12M	6	12	6.2	11.8	4.5	1600	1255	5000	7000	8	2
F6-14M	6	14	6.25	13.8	5	1800	1588	4000	7000	8	2.381
F7-13M	7	13	7.2	16.8	4.5	1422	1255	4000	7000	9	2
F7-15M	7	15	7.2	14.8	5	2200	2000	3600	7100	8	2.5
F7-17M	7	17	7.2	16.8	6	2600	2256	3500	7000	8	2.381
F8-16M	8	16	8.2	15.8	5	2500	3000	4000	8000	9	3
F8-19M	8	19	8.2	18.8	7	3452	3000	3000	5000	8	3.175
F9-20M	9	20	9.2	19.8	7	3356	2999	2500	4500	8	3.175
F10-18M	10	18	10.2	17.8	5.5	2230	2721	2500	4500	10	2.381

TBP No.	Dimensions (Metric)			Appr ox.	Interchange			
	d	D	B		Wgt.	ADR	ISC	Nachi
<u>F3-8M</u>	3	8	3.5	0.002	B3	-	3TAM8	B308
<u>F4-9M</u>	4	9	4	0.003	-	-	4TAM9	-
<u>F4-10M</u>	4	10	4	0.003	B4	-	5TAM10	B410
<u>F5-12M</u>	5	12	4	0.003	B5	-	-	B512
<u>F6-12M</u>	6	12	4.5	0.004	-	-	6TAM12	-
<u>F6-14M</u>	6	14	5	0.008	B6	-	-	B614
<u>F7-13M</u>	7	13	4.5	0.004	-	-	-	-
<u>F7-14M</u>	7	14	4.5	0.005	-	-	7TAM14	-
<u>F7-17M</u>	7	17	6	0.01	B7	-	-	B717
<u>F8-16M</u>	8	16	5	0.008	-	-	8TAM16	-
<u>F8-19M</u>	8	19	7	0.016	B8	-	-	B819
<u>F9-20M</u>	9	20	7	0.022	B9	-	-	B920
<u>F10-18M</u>	10	18	5.5	0.026	-	-	-	-